

# HHR Configuration for Magellan 2xxx / 8xxx / 9xxx AUX-Port

## HHR Konfiguration für Magellan 2xxx / 8xxx / 9xxx AUX-Port


Cable: CAB-362 SH3924 (90G001092)

### Restore Default




\$+\$\*

### RS232 – 9600/8/N/1 – RTS/CTS



\$+CPOCE1\$-

### Inter-Character Delay



\$+CKO2\$-

### Disable Terminator



\$+EA10\$-

### Enable Custom Code Identifier



\$+EB3\$-

### Set Code Identifier UPC-A “A”



\$+EHC41FF\$-

### Set Code Identifier UPC-E “E”



\$+EHD45FF\$-

### Set Code Identifier EAN-13 “F”



\$+EHB46FF\$-

### Set Code Identifier EAN-8 “FF”



\$+EHA4646\$-

**Optional: CODE 128, CODE 39, CODE 93, INTERLEAVED 2/5, PDF 417, EAN 128**

**Set Code Identifier CODE 128 "K"**



**Set Code Identifier CODE 39 "\*\*\*"**



**CODE 39 append trailing \***



**Set Code Identifier CODE 93 "&"**



**Set Code Identifier INTERLEAVED 2/5 "i"**



**Set Code Identifier PDF 417 "P"**



**Optional: Enable Code EAN 128 & Set Code Identifier EAN-128 "[C1]"**



**2xxx / 8xxx / 9xxx Handheld Port Enable**  
**(Please read this with the Magellan!)**  
**(Bitte dies mit dem Magellan lesen!)**

Enable HandHeld Port

